

- **Alliance**

- **G2 Super Sand**

- Description

- **SUPERSAND G2** is made with a state-of-the-art manufacturing process. Specifically, calibrated sand is mixed with sophisticated intelligent polymers. This new generation of Intelligent Polymers neutralizes haze and dust. No blower is needed, and the intelligent polymeric sand requires only one watering. **SUPERSAND G2** is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc. Available in Beige and Slate Grey.

- Features

- Can be used for joints up to a maximum of 5 cm (2 in) and its fine gradation allows use in even the tightest joints.
- Helps prevent weeds and damage caused by burrowing insects.
- Helps prevent erosion due to wind, rain and freeze/thaw cycles.
- **SUPERSAND G2** sets within 1 hour after water activation at above 0 C (32°F), (no rain within 1hour after water activation).
- **No Dust, Haze Free, No Blower, and one watering.**
- Intact pallets can be stored outside.

- **CLAY PAVERS**

- If used on clay pavers, make sure they are 100% dry. Clay pavers tend to hold moisture which can prematurely activate the **SUPERSAND G2** while the sand is being spread over the paver surface, leaving a residue. Always apply on a test area before using the **SUPERSAND G2** on clay pavers.

- **MOSS**

- **SUPERSAND G2** will not cause nor prevent moss, mold or mildew. Moss, mold and mildew are caused by certain on-site conditions including excess moisture, shade, absence of ventilation, inadequate cleaning or maintenance, presence of soil or other organic debris left on the product.

- **COVERAGE**

- Quantity required depends on the shape and size of the concrete pavers as well as the width of the joints.

	NARROW JOINTS		WIDE JOINTS	
	sq. m.	sq. ft.	sq. m.	sq. ft.
Beige, Slate Grey 50 lbs / 22.7 kg	6.00-7.41	65-85	2.00-3.88	22-42

HELPS PREVENT



Helps prevent weed sprouting.



Helps prevent damages caused by insects.



Helps prevent erosion due to climatic conditions, such as wind, rain and freezing temperatures.

2 BEAUTIFUL COLORS TO CHOOSE FROM



FOR USE ON AND REQUIRED SUB-SURFACE PREPARATION

SUPERSAND G2 is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc. The concrete pavers must be installed on a drainage base system composed of 2 layers. The upper layer can have a maximum of 2,5 cm (1 inch) of bedding sand. The lower layer must have a minimum of 15 cm (6 inches) of crushed stone compacted at 98 % Proctor density.