

- **Alliance**
 - **Gator Maxx Bond**

DESCRIPTION

Gator Maxx Sand is a unique mixture of polymer binders and calibrated sand available in Beige, Slate Grey. The installation of **Gator Maxx Sand** is almost identical to using regular paver joint sand except for the application of water. Once **Gator Maxx Sand** sets, it becomes very firm and locks between the paver joints while still retaining flexibility and providing a long lasting, durable jointing material. **Gator Maxx Sand** is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements etc.

FEATURES

- Can be used on false joint pavers
- For overlay, non-overlay, residential and commercial applications
- Can be used for joints up to a maximum of 2 inches (5 cm)
- Helps prevent weeds and damage caused by burrowing insects
- Helps prevent erosion due to wind, rain, and freeze thaw cycles
- Fast setting: Product sets within one hour after application of water
- Sets at above freezing temperatures (32°F/ 0°C)
- Can be applied even if rain is expected (however, minimum of 1 hour of dry weather is needed after activation)
- Non-drainage base systems, minimum of 24 hours without rain
- Advanced Haze Free Technology
- Intact pallets can be stored outside
- Ideal for Gator Base panels

HELPS PREVENT



Helps prevent weed sprouting.



Helps prevent damages caused by insects.



Helps prevent erosion due to climatic conditions, such as wind, rain and freezing temperatures.

2 BEAUTIFUL COLORS TO CHOOSE FROM



COVERAGE

Quantity required depends on the shape and size of _____ the concrete pavers as well as the width of the joints.

	NARROW JOINTS		WIDE JOINTS	
	m ²	ft ²	m ²	ft ²
Slate Grey, Beige 50 lbs (22.7 kg)	6.00-7.41	65-85	2.00-3.88	22-42

PACKAGING

PRODUCTS	RETAIL SIZE	UNITS PER PALLET
Gator Maxx Sand – Beige	22.7 kg (50 lbs)	56
Gator Maxx Sand – Slate Grey	22.7 kg (50 lbs)	56

- Plastic bags
- Intact pallets can be stored outside