

- **Alliance**

- **Gator Max G2**

- Description

- **GATOR MAXX G2** is made with a state-of-the-art manufacturing process. Specifically, calibrated sand is mixed with sophisticated intelligent polymers. This new generation of Intelligent Polymers neutralizes haze and dust. The polymeric sand application is now dust free and haze free. No blower is needed, and the intelligent polymeric sand requires only one watering. **GATOR MAXX G2** is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc. Available in Beige, Slate Grey, Ivory and Black Diamond

- Features

- Can be used on false joint pavers.
- For overlay, non-overlay, residential and commercial applications.
- Can be used for joints up to a maximum of 4 inches.
- Helps prevent weeds and damage caused by burrowing insects.
- Helps prevent erosion due to wind, rain and freeze/thaw cycles.
- For **NON-OVERLAY**, **G2** sets within 1 hour after water activation at above 32°F, (no rain within 1 hour after water activation)
- For **OVERLAY**, **G2** sets within 1 hour after water activation at above 32°F (no rain within 24 hours after water activation)
- **No Dust, Haze Free, No Blower, and one watering.**
- Intact pallets can be stored outside.
- Ideal for Gator Base applications.

- **CLAY PAVERS**

- If used on clay pavers, make sure they are 100% dry. Clay pavers tend to hold moisture which can prematurely activate the **GATOR MAXX G2** while the sand is being spread over the paver surface, leaving a residue. Always apply on a test area before using the **GATOR MAXX G2** on clay pavers.

- **MOSS**

- **GATOR MAXX G2** will not cause nor prevent moss, mold or mildew. Moss, mold and mildew are caused by certain on-site conditions including excess moisture, shade, absence of ventilation, inadequate cleaning or maintenance, presence of soil or other organic debris left on the product.

- **COVERAGE**

- Quantity required depends on the shape and size of _____ the concrete pavers as well as the width of the joints.

	NARROW JOINTS		WIDE JOINTS	
	sq. m.	sq. ft.	sq. m.	sq. ft.
Beige, Slate Grey, Ivory 50 lbs / 22.7 kg	6.00-7.41	65-85	2.00-3.88	22-42
Black Diamond 50 lbs / 22.7 kg	5.50-6.5	58-76	1.8-3.5	20-38

HELPS PREVENT



Helps prevent weed sprouting. _____



Helps prevent damages caused by insects.



Helps prevent erosion due to climatic conditions, such as wind, rain and freezing temperatures.

4 BEAUTIFUL COLORS TO CHOOSE FROM



BEIGE

SLATE GREY

IVORY

BLACK DIAMOND

GATOR MAXX G2 is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements, etc. The concrete pavers must be installed on a drainage base system composed of 2 layers. The upper layer can have a maximum of 1 inch of bedding sand. The lower layer must have a minimum of 6 inches of crushed stone compacted at 98 % Proctor density.

FOR OVERLAY APPLICATIONS

- Remove all loose and fragile concrete.
- Cover the ground with a geotextile, refill with crushed stone and compact it.