

- **Alliance**
 - **Gator Super Sand Bond**

DESCRIPTION

Supersand Bond is a unique mixture of polymer binders and calibrated sand available in Beige, Slate Grey. The installation of **Supersand Bond** is almost identical to using regular paver joint sand except for the application of water. Once **Supersand Bond** sets, it becomes very firm and locks between the paver joints while still retaining flexibility and providing a long lasting, durable jointing material. **Supersand Bond** is recommended for a variety of uses including pool decks, patios, footpaths, driveways, parking spaces, pavements etc.

FEATURES

- Advanced Haze Free Technology
- Waterproof Bag
- Can be used for joints up to a maximum of 1 inch (2.5 cm) and its fine gradation allows use_____ in even the tightest joints
- Helps prevent weeds and damage caused by burrowing insects
- Helps prevent erosion due to wind, rain, and freeze thaw cycles
- Fast setting: Product sets within one hour after application of water
- Sets at above freezing temperatures (32°F/ 0°C)
- Can be applied even if rain is expected (however, minimum of 1 hour of dry weather is needed after activation)
- Pallets can be stored outside

COVERAGE

	NARROW JOINTS		WIDE JOINTS	
	m ²	ft ²	m ²	ft ²
Slate Grey, Beige 50 lbs (22.7 kg)	6.00-7.41	65-85	2.00-3.88	22-42

Quantity required depends on the shape and size of_____ the concrete pavers as well as the width of the joints.

PACKAGING

PRODUCTS	RETAIL SIZE	UNITS PER PALLET
Gator Super Sand Bond – Beige	22.7 kg (50 lbs)	56

Gator Super Sand Bond – Slate Grey

22.7 kg (50 lbs)

56

All Alliance Polymeric sand can be stored outside

New waterproof bag, an advanced progressive solution for long-term storage of **Gator Polymeric Sand and Dust** products. Whether winter, spring, summer, or fall your polymeric sand and dust is protected.

HELPS PREVENT



Helps prevent weed sprouting.



Helps prevent damages caused by insects.



Helps prevent erosion due to climatic conditions, such as wind, rain and freezing temperatures.

2 BEAUTIFUL COLORS TO CHOOSE FROM

